

Ebara hjámiðjudælar 2 CDX

Dælugerð		Afl kW	l/mín m ³ /klst	Vinnslugeta = Q								
				0	20	40	60	80	120	150	180	210
1 fasa	3 fasa			0	1,2	2,4	3,6	4,8	7,2	9,0	10,8	12,6
				H = Heildar lyftigeta í m								
2CDXM 70/10	2CDX 70/10	0,75		41,0	38,5	35,3	31,5	27,0	-	-	-	-
2CDXM 70/12	2CDX 70/12	0,90		48,0	44,5	40,3	35,5	30,0	-	-	-	-
2CDXM 70/15	2CDX 70/15	1,10		56,0	52,5	48,0	42,8	36,5	-	-	-	-
2CDXM 70/20	2CDX 70/20	1,50		64,0	60,0	55,6	50,4	44,0	-	-	-	-
2CDXM 120/15	2CDX 120/15	1,10		46,0	-	42,0	41,0	39,5	35,0	30,0	-	-
2CDXM 120/20	2CDX 120/20	1,50		55,0	-	51,5	49,5	47,4	41,8	36,5	-	-
-	2CDX 120/30	2,20		63,0	-	59,0	57,0	54,6	49,2	44,0	-	-
-	2CDX 120/40	3,00		71,5	-	68,5	66,5	64,0	58,0	52,0	-	-
-	2CDX 200/30	2,20		55,0	-	-	52,0	50,8	48,1	45,5	42,7	39,5
-	2CDX 200/40	3,00		66,0	-	-	62,5	61,1	58,0	55,2	52,3	49,0
-	2CDX 200/50	3,70		75,0	-	-	71,5	70,1	67,0	64,3	61,2	57,5