



MVE 2400/15

Three Phases - 4 poles - 1500 RPM - 50 Hz
230/400 Volt



Mechanical Features		Electric Features	
General		General	
Working Moment	187.69 kgcm	Nominal Voltage	Δ : 230 V Y : 400 V
Unbalance	93.84 kgcm	Input Power	1.6 kW
FC	2358 kg	Current A Max	Δ : 5.22 A Y : 3 A
Bearings		Power factor	0.75
TYPE (SKF)	NJ 2307	Ia/In	4,9
	100% 7490	Certification	
Life(h)	80%: 15759	ETL CLASS II DIV.II GROUP F,G TENV NEMA 4	T4
	50%: 75498	ATEX II 3D Ex tc IIIC Tx IP66	T 135°
Bearing Grease		Amb Temp.	-20 ≤ T°C ≤ + 40
Lube Schedule (g)	13		
Lube Replacement (g)	25		
Grease Type	SKF LGHP2		

Dimensional Features (mm)

Fig. D		A	140		
		B	190		
		C	510		
		M	129		
		G	17		
		holes	4		
		D	229		
		E	247		
		F	30		
		H	120		
		I	262		
		L	220		
		N	222		
		Clamping Torque(Nm)			
		185	[Drawings Download]		

Weight(kg)	Screw	Washer	Cable Type	Cable Glандe
68	M16	17x30	4Gx4	M25x1,5

REV.2-03/10/2013