



Gerð	Dæla	Hámarks afl kW	Stilling þrýstirofa BAR	Hámarks hæð m	Flæði l/klst	Stærð tanks l	Inngangur "	Útgangur "
TK1-TR1	KF1	0.37	1.3V2.8	13	1.300	24	1	1
TK2-TR2	KF2	0.55	2V4.2	27	1.900	24	1	1
TK3-TR3	M60	0.37	1.8V4	25	1.800	24	1	1
TK4-TR4	M70	0.55	2.4V4.2	27	2.000	24	1	1
TK5-TR5	M80	0.75	2V4.4	29	2.100	24	1	1
TK6-TR6	M150	1.1	4.5V5.3	38	2.250	24/60	1 1/2	1
TK7-TR7	M200	1.5	4.3V5.5	40	2.800	24/60	1 1/2	1
TK8-TR8	CMP79	0.75	1.8V3.1	16	3.600	24	1	1
TK9-TR9	CM1	1.1	2V3.5	20	4.400	24	1	1
TK10-TR10	FC20-2A	0.75	2.4V3.7	22	3.100	24	1	1
TK11-TR11	FC25-2D	1.1	2.4V3.5	20	4.200	24	1 1/4	1
TK12-TR12	FC25-2C	1.5	3.3V4.7	32	4.800	24	1 1/4	1
TKX3-TRX3	M94	0.37	1.8V4	25	1.800	24	1	1
TKX4-TRX4	M97	0.55	2.4V4.2	27	2.000	24	1	1
TKXS-TRXS	M99	0.75	2V4.4	29	2.100	24	1	1