

Submersible Dewatering Pumps





Dewatering Solutions for the Real World


In the real world time is money, and worksites have no time for unwanted water. Sulzer has the solutions in a complete pump range for reliable dewatering.

This brochure is an overview of Sulzer's submersible dewatering pumps, which are the result of more than 50 years of technical and real-world experience. Each pump type is presented with its key features, as well as dimensions, performance curves and the most important technical data for specific pump models.

Whether you work in mining, tunneling or construction, the pumps here are your best insurance against water-related downtime. From purchasing to service, you can turn to Sulzer for dewatering solutions that make a difference in the real world.

| CONTENT | PAGE |
|--|-------------|
| Dewatering Solutions for the Real World | 3 |
| Submersible Drainage Pumps | |
| J (small) | 4-5 |
| XJ (medium) | 6-7 |
| J (large) | 8-9 |
| Submersible Drainage Center-Line Pumps | |
| JC and XJC | 10-11 |
| Submersible Sludge Pumps | |
| JS | 12-13 |
| XJS | 14-15 |
| AquaTronic and Other Supervision Options | 16 |
| Overview of Electronic Supervision Features | 17 |
| Pump Options and Accessories | 18-19 |

Performance range 50 Hz



Sulzer's complete range of submersible dewatering pumps provides reliable solutions for all major dewatering needs.

Submersible Drainage Pump J

Submersible drainage pump J is suitable for pumping water and dirty water mixed with light abrasives. The low weight and compact design makes for convenient transport, handling and installation.

1 Easy start

A built-in contactor connected to the thermal sensors in the stator windings protects the motor from overheating and features an automatic restart function.

2 Wear resistance


An impeller in white cast iron with a full upper shroud and adjustable wear parts coated in nitrile rubber ensure high abrasion resistance.

3 Reliable operation

A double mechanical shaft seal in an oil bath, with primary and secondary seal surfaces in silicon carbide, extends the life of the pump. A double outer casing and good heat convection enable the pump to operate continuously at low levels – or even run dry without damaging the motor.



4 Serviceability

Due to the modular design, the same parts can be used for different pumps, which lowers the overall service costs. An adjustable diffuser ensures proper clearance throughout the impeller lifetime. By removing the top cover of the pump, the electrical junction area can easily be checked.





SUBMERSIBLE DRAINAGE PUMP J 5

| J 5 W | 1-PHASE |
|-----------------------|----------------------------|
| Motor rating P2 | 0.48 kW, 1~ |
| Voltage (V) | 230 |
| Full load (A) | 2.9 |
| Speed | 2690 rpm |
| Strainer hole | 6 mm |
| Discharge connections | Hose 2" Thread G/BSP 2" |
| Weight (excl. cable) | 9.5 kg |
| Motor protection | Built-in |
| Electric cable | 10 m |





SUBMERSIBLE DRAINAGE PUMP J 12

| J 12 W/J 12 WKS* J 12 D/J 12 DKS** | 1-PHASE | 3-PHASE |
|---------------------------------------|---|-----------------|
| Motor rating P2 | 0.9 kW, 1~ | 1 kW, 3~ |
| Voltage (V) | 110 / 230 | 230 / 400 / 500 |
| Full load (A) | 10.9 / 5.2 | 4.0 / 2.3 / 1.9 |
| Speed | 2750 rpm | 2800 rpm |
| Strainer hole | 6.5 x 22 mm | |
| Discharge connections | Hose 1½", 2", 2½", 3" Thread G/BSP 2", 2½", 3" | |
| Weight (excl. cable) | 16 kg | |
| Motor protection | Built-in | |
| Electric cable | 20 m | |



SUBMERSIBLE DRAINAGE PUMP J 15

| J 15 W/J 15 WKS* J 15 D/J 15 DKS** | 1-PHASE | 3-PHASE |
|---------------------------------------|---|-----------------|
| Motor rating P2 | 1.4 kW, 1~ | 1.4 kW, 3~ |
| Voltage (V) | 230 | 230 / 400 / 500 |
| Full load (A) | 8.1 | 5.0 / 2.9 / 2.3 |
| Speed | 2800 rpm | 2800 rpm |
| Strainer hole | 6.5 x 22 mm | |
| Discharge connections | Hose 1½", 2", 2½", 3" Thread G/BSP 2", 2½", 3" | |
| Weight (excl. cable) | 18 kg (W), 16.5 kg (D) | |
| Motor protection | Built-in | |
| Electric cable | 20 m | |



* Built-in float switch available as option.
** KS version not available in 500 V.

Submersible Drainage Pump XJ

Submersible drainage pump XJ is excellent for pumping water and dirty water mixed with light abrasives. The slim design makes the pump easy to move and easy to handle.

1 Easy and fail-safe starting

Instead of a built-in contactor, an optional AquaTronic unit can be used. The AquaTronic unit compensates for incorrect phase order, which ensures correct motor rotation every time. (Additional AquaTronic functions for electronic supervision are explained on pages 16-17.)

2 Wear resistance

An impeller and wear ring in white cast iron, as well as diffusers coated in oil-resistant nitrile rubber, provide high abrasion resistance.

3 Reliable operation

Double mechanical shaft seals in an oil bath, with primary seal surfaces in silicon carbide and secondary seal surfaces in silicon carbide on carbon, extend the life of the pump. A double cable-entry seal system increases the protection against moisture entering the electrical junction area. A double outer casing and good heat convection enable the pump to operate continuously at low levels – or even run dry without damaging the motor.

4 Serviceability


Due to the modular design, the same parts can be used for different pumps, which lowers the overall service costs. The adjustable wear ring ensures proper clearance throughout the impeller lifetime. External inspection ports for the oil and motor chambers enable quick and easy evaluation of the shaft seal during service. By removing the top cover of the pump, the electrical junction area can easily be checked.

5 Less energy and environmental impact

The high-efficiency motor and new hydraulics combine with low-friction bearings to reduce power losses. The result is low total energy costs and minimized carbon footprint.



6 Flexibility

Conversion between high-volume and high-head hydraulics is managed with only a few parts, ensuring the right performance for the application.





SUBMERSIBLE DRAINAGE PUMP XJ 25

| XJ 25 ND* XJ 25 HD* | MEDIUM HEAD HIGH HEAD |
|------------------------|--|
| Motor rating P2 | 2.5 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 8.8 / 5.1 / 4.3 / 2.9 / 2.0 |
| Speed | 2920 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 2½", 3", 4" Thread G/BSP 2½", 3", 4" |
| Weight (excl. cable) | 39 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |





SUBMERSIBLE DRAINAGE PUMP XJ 40

| XJ 40 ND* XJ 40 HD* | MEDIUM HEAD HIGH HEAD |
|------------------------|--|
| Motor rating P2 | 3.7 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 13.2 / 7.6 / 6.1 / 4.4 / 3.0 |
| Speed | 2860 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 2½", 3", 4" Thread G/BSP 2½", 3", 4" |
| Weight (excl. cable) | 42 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |





SUBMERSIBLE DRAINAGE PUMP XJ 50

| XJ 50 ND* XJ 50 LD* XJ 50 HD* | MEDIUM HEAD HIGH FLOW HIGH HEAD |
|-------------------------------------|--|
| Motor rating P2 | 5.6 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 19.7 / 11.3 / 9.0-10.8 / 6.6 / 4.5 |
| Speed | 2930 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 3", 4", 6" Thread G/BSP 3", 4", 6" |
| Weight (excl. cable) | 59 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |





SUBMERSIBLE DRAINAGE PUMP XJ 80

| XJ 80 ND* XJ 80 LD* XJ 80 SD* | MEDIUM HEAD HIGH FLOW HIGH HEAD |
|-------------------------------------|--|
| Motor rating P2 | 8.3 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 27.8 / 16 / 13.8 / 9.3 / 6.4 |
| Speed | 2920 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 3", 4", 6" Thread G/BSP 3", 4", 6" |
| Weight (excl. cable) | 63 kg (ND/LD), 78 kg (SD) |
| Motor protection | Built-in |
| Electric cable | 20 m |



SUBMERSIBLE DRAINAGE PUMP XJ 110

| XJ 110 ND* XJ 110 HD* | MEDIUM HEAD HIGH HEAD |
|--------------------------|--|
| Motor rating P2 | 11.8 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 37.4 / 21.5 / 17.2 / 12.5 / 8.6 |
| Speed | 2920 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 3", 4", 6" Thread G/BSP 3", 4", 6" |
| Weight (excl. cable) | 81 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



* Option: AquaTronic, built-in electronic pump control.
** Max measurement based on largest discharge size.

Submersible Drainage Pump J

Submersible drainage pump J is suitable for pumping water and dirty water mixed with light abrasives. The pump design enables convenient transport, handling and installation.

1 Easy to start

Pump J 205 has a built-in contactor connected to the thermal sensors in the stator windings, which protects the motor from overheating and features an automatic restart function. Pumps J 405 and J 604 have thermal sensors in the stator windings that protect the motor from overheating by means of an external control panel.

2 Wear resistance

Abrasive-resistant impellers, combined with diffusers and wear rings coated in oil-resistant nitrile rubber, provide extended pump life in tough applications.

3 Reliable operation


Double mechanical shaft seals in an oil bath, with primary seal surfaces in silicon carbide, extend the life of the pump. In pumps J 205 and J 405, the primary and secondary seals comprise an easy-to-replace seal cartridge. A double outer casing and good heat convection enable the pump to operate continuously at low levels – or even run dry without damaging the motor.

4 Serviceability

External inspection ports for the oil and motor chambers enable quick and easy evaluation of the shaft seal during service. By removing the top cover of the pump, the electrical junction area can easily be checked. The adjustable wear ring ensures proper clearance throughout the impeller lifetime.



5 Flexibility

Conversion between high-volume and high-head hydraulics is managed with only a few parts, ensuring the right performance for the application.





SUBMERSIBLE DRAINAGE PUMP J 205

| J 205 ND | MEDIUM HEAD |
|-----------------------|--|
| J 205 HD | HIGH HEAD |
| Motor rating P2 | 21 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 68 / 39 / 31.2 / 23 / 16 |
| Speed | 2910 rpm |
| Strainer hole | 8 x 34 mm |
| Discharge connections | Hose 4", 6", 8" Thread G/BSP 4", 6", 8" |
| Weight (excl. cable) | 155 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |





SUBMERSIBLE DRAINAGE PUMP J 405

| J 405 ND | MEDIUM HEAD |
|-----------------------|--|
| J 405 HD | HIGH HEAD |
| Motor rating P2 | 35 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 108 / 62 / 51 / 36 / 25 |
| Speed | 2930 rpm |
| Strainer hole | 8 x 34 mm |
| Discharge connections | Hose 4", 6", 8" Thread G/BSP 4", 6", 8" |
| Weight (excl. cable) | 270 kg |
| Motor protection | Thermal overload sensors |
| Electric cable | 20 m |



SUBMERSIBLE DRAINAGE PUMP J 604

| J 604 ND | MEDIUM HEAD |
|-----------------------|---|
| J 604 HD | HIGH HEAD |
| Motor rating P2 | 56 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 184 / 106 / 84 / 61 / 42 |
| Speed | 1450 rpm |
| Strainer hole | 12 x 60 mm |
| Discharge connections | Hose 6", 8", 10" Thread G/BSP 6", 8" |
| Weight (excl. cable) | 525 kg |
| Motor protection | Thermal overload sensors |
| Electric cable | 20 m |



Submersible Drainage Center-Line Pumps JC and XJC

Submersible drainage center-line pumps JC and XJC are excellent for pumping water and dirty water mixed with light abrasives. The slim design makes them easy to move and easy to handle, and they are perfect for applications with limited installation space.

1 Easy and fail-safe starting

In XJC pump models, an optional AquaTronic unit can be used instead of a built-in contactor. The AquaTronic unit compensates for incorrect phase order, which ensures correct motor rotation every time. (Additional AquaTronic functions for electronic supervision are explained on pages 16-17.) In JC pump models, a built-in contactor with an automatic restart function protects the motor.

2 Wear resistance

An impeller and wear ring in white cast iron, as well as diffusers coated in oil-resistant nitrile rubber, provide high abrasion resistance.

3 Reliable operation

Double mechanical shaft seals in an oil bath, with primary seal surfaces in silicon carbide and secondary seal surfaces in silicon carbide on carbon, extend the life of the pump. Pumps XJC 50 - XJC 110 have a double cable-entry seal system that increases the protection against moisture entering the electrical junction area. A double outer casing and good heat convection enable the pump to operate continuously at low levels – or even run dry without damaging the motor.

4 Serviceability

Due to the modular design, the same parts can be used for different pumps, which lowers the overall service costs. The adjustable wear ring ensures proper clearance throughout the impeller lifetime. External inspection ports for the oil and motor chambers enable quick and easy evaluation of the shaft seal during service. By removing the top cover of the pump, the electrical junction area can easily be checked.

5 Less energy and environmental impact

Pumps XJC 50 - XJC 110 are equipped with high-efficiency motors and new hydraulics, which combine with low-friction bearings to reduce power losses. The result is low total energy costs and minimized carbon footprint.



6 Flexibility

Pumps XJC 50 - XJC 110 allow conversion between high-volume and high-head hydraulics with only a few parts, ensuring the right performance for the application.





SUBMERSIBLE DRAINAGE CENTER-LINE PUMP JC 34

| JC 34 ND JC 34 HD | MEDIUM HEAD HIGH HEAD |
|-----------------------|------------------------------------|
| Motor rating P2 | 3 kW, 3~ |
| Voltage (V) | 230 / 400 / 500 |
| Full load (A) | 12.7 / 7.3 / 5.5 |
| Speed | 2850 rpm |
| Strainer hole | 8 x 33 mm |
| Discharge connections | Hose 2", 3" Thread G/BSP 2", 3" |
| Weight (excl. cable) | 31 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |





SUBMERSIBLE DRAINAGE CENTER-LINE PUMP XJC 50

| XJC 50 ND* XJC 50 LD* XJC 50 HD* | MEDIUM HEAD HIGH FLOW HIGH HEAD |
|--|--|
| Motor rating P2 | 5.6 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 19.7 / 11.3 / 9.0-10.8 / 6.6 / 4.5 |
| Speed | 2930 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 3", 4", 6" Thread G/BSP 3", 4", 6" |
| Weight (excl. cable) | 59 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |





SUBMERSIBLE DRAINAGE CENTER-LINE PUMP XJC 80

| XJC 80 ND* XJC 80 LD* XJC 80 SD* | MEDIUM HEAD HIGH FLOW HIGH HEAD |
|--|--|
| Motor rating P2 | 8.3 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 27.8 / 16 / 13.8 / 9.3 / 6.4 |
| Speed | 2920 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 3", 4", 6" Thread G/BSP 3", 4", 6" |
| Weight (excl. cable) | 63 kg (ND/LD), 78 kg (SD) |
| Motor protection | Built-in |
| Electric cable | 20 m |



SUBMERSIBLE DRAINAGE CENTER-LINE PUMP XJC 110

| XJC 110 ND* XJC 110 HD* | MEDIUM HEAD HIGH HEAD |
|----------------------------|--|
| Motor rating P2 | 11.8 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 37.4 / 21.5 / 17.2 / 12.5 / 8.6 |
| Speed | 2920 rpm |
| Strainer hole | 7.5 x 22 mm |
| Discharge connections | Hose 3", 4", 6" Thread G/BSP 3", 4", 6" |
| Weight (excl. cable) | 80 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



* Option: AquaTronic, built-in electronic pump control.

Submersible Sludge Pump JS

Submersible sludge pump JS is excellent for pumping dirty water and water mixed with solids. The pump has a slim design and low weight, which makes it easy to move and easy to handle.

1 Easy to start

A built-in contactor connected to the thermal sensors in the stator windings protects the motor from overheating and features an automatic restart function.

2 Clog-free pumping

A free-flow vortex impeller and pump volute make the pump ideal for pumping solids. The impeller is available in different sizes to meet specific requirements.

3 Reliable operation


Both the impeller and volute are made from heavy-duty ductile iron for maximum durability. Double mechanical shaft seals in an oil bath, with primary and secondary seal surfaces in silicon carbide, extend the life of the pump.

4 Convenient handling

The top cover and motor housing are made of light-weight aluminum, which creates a pump that is very easy to handle and install.

5 Serviceability



Due to the modular design, the same parts can be used for different pumps, which lowers the overall service costs. External inspection ports for the oil and motor chambers enable quick and easy evaluation of the shaft seal during service. By removing the top cover of the pump, the electrical junction area can easily be checked.



SUBMERSIBLE SLUDGE PUMP JS 12

| | | |
|--------------------------|----------------|----------------|
| JS 12 W/WKS* -104 | 1-PHASE | |
| JS 12 W/WKS* -114 | 1-PHASE | |
| JS 12 D/DKS* -104 | | 3-PHASE |
| JS 12 D/DKS* -114 | | 3-PHASE |



| | | |
|-----------------------|--|-----------------|
| Motor rating P2 | 0.9 kW, 1~ | 0.9 kW, 3~ |
| Voltage (V) | 230 | 230 / 400 / 500 |
| Full load (A) | 5.1 | 3.3 / 1.9 / 1.5 |
| Speed | 2850 rpm | 2850 rpm |
| Free passage | 45 x 40 mm | |
| Discharge connections | Hose 2", 2½", 3" Thread G/BSP 2", 2½", 3" | |
| Weight (excl. cable) | 18 kg | |
| Motor protection | Built-in | |
| Electric cable | 20 m | |



SUBMERSIBLE SLUDGE PUMP JS 15

| | |
|-------------------------|----------------|
| JS 15D/DKS* -114 | 3-PHASE |
| JS 15D/DKS* -126 | 3-PHASE |

| | |
|-----------------------|--|
| Motor rating P2 | 1.3 kW, 3~ |
| Voltage (V) | 230 / 400 / 500 |
| Full load (A) | 4.5 / 2.6 / 2.1 |
| Speed | 2850 rpm |
| Free passage | 45 x 40 mm |
| Discharge connections | Hose 2", 2½", 3" Thread G/BSP 2", 2½", 3" |
| Weight (excl. cable) | 18 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



* Built-in float switch available as option. KS version not available in 500 V.



Submersible Sludge Pump XJS

Submersible sludge pump XJS is excellent for pumping dirty water and water mixed with solids. The slim design makes the pump easy to move and easy to handle.

1 Easy and fail-safe starting

Instead of a built-in contactor, an optional AquaTronic unit can be used. The AquaTronic unit compensates for incorrect phase order, which ensures correct motor rotation every time. (Additional AquaTronic functions for electronic supervision are explained on pages 16-17.)

2 Clog-free pumping

A free-flow vortex impeller and pump volute make the pump ideal for pumping solids. The impeller is available in different sizes to meet specific requirements.

3 Reliable operation

Both the impeller and volute are made from heavy-duty ductile iron for maximum durability. Double mechanical shaft seals in an oil bath, with primary seal surfaces in silicon carbide and secondary seal surfaces in silicon carbide on carbon, extend the life of the pump. A double cable-entry seal system increases the protection against moisture entering the electrical junction area.

4 Convenient handling


The top cover and motor housing are made of lightweight aluminum, which creates a pump that is very easy to handle and install.

5 Serviceability

Due to the modular design, the same parts can be used for different pumps, which lowers the overall service costs. External inspection ports for the oil and motor chambers enable quick and easy evaluation of the shaft seal during service. By removing the top cover of the pump, the electrical junction area can easily be checked.

6 Less energy and environmental impact



The high-efficiency motor and hydraulics combine with low-friction bearings to reduce power losses. The result is low total energy costs and minimized carbon footprint.



SUBMERSIBLE SLUDGE PUMP XJS 25

XJS 25 D* -128
XJS 25 D* -143



| | |
|-----------------------|--|
| Motor rating P2 | 2.5 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 8.8 / 5.1 / 4.3 / 2.9 / 2.0 |
| Speed | 2920 rpm |
| Free passage | 45 x 55 mm |
| Discharge connections | Hose 2½", 3", 4" Thread G/BSP 2½", 3", 4" |
| Weight (excl. cable) | 39 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



SUBMERSIBLE SLUDGE PUMP XJS 40

XJS 40 D* -143
XJS 40 D* -160



| | |
|-----------------------|--|
| Motor rating P2 | 3.7 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 13.2 / 7.6 / 6.1 / 4.4 / 3.0 |
| Speed | 2860 rpm |
| Free passage | 45 x 55 mm |
| Discharge connections | Hose 2½", 3", 4" Thread G/BSP 2½", 3", 4" |
| Weight (excl. cable) | 41 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



SUBMERSIBLE SLUDGE PUMP XJS 50

XJS 50 D* -160
XJS 50 D* -175



| | |
|-----------------------|--|
| Motor rating P2 | 5.6 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 19.7 / 11.3 / 9.0 / 6.6 / 4.5 |
| Speed | 2930 rpm |
| Free passage | 48 x 60 mm |
| Discharge connections | Hose 2½", 3", 4" Thread G/BSP 2½", 3", 4" |
| Weight (excl. cable) | 59 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



SUBMERSIBLE SLUDGE PUMP XJS 80

XJS 80 D* -175
XJS 80 D* -195



| | |
|-----------------------|--|
| Motor rating P2 | 8.3 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 27.8 / 16 / 12.8 / 9.3 / 6.4 |
| Speed | 2920 rpm |
| Free passage | 48 x 60 mm |
| Discharge connections | Hose 2½", 3", 4" Thread G/BSP 2½", 3", 4" |
| Weight (excl. cable) | 64 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



SUBMERSIBLE SLUDGE PUMP XJS 110

XJS 110 D* -170
XJS 110 D* -195

| | |
|-----------------------|--|
| Motor rating P2 | 11.8 kW, 3~ |
| Voltage (V) | 230 / 400 / 500-550 / 690 / 1000 |
| Full load (A) | 37.4 / 21.5 / 17.2 / 12.5 / 8.6 |
| Speed | 2920 rpm |
| Free passage | 48 x 60 mm |
| Discharge connections | Hose 2½", 3", 4" Thread G/BSP 2½", 3", 4" |
| Weight (excl. cable) | 80 kg |
| Motor protection | Built-in |
| Electric cable | 20 m |



* Option: AquaTronic, built-in electronic pump control.

AquaTronic and Other Supervision Options

Submersible dewatering pumps XJ, XJC and XJS have several options for electronic supervision that make them even more reliable and easy to use. Most important is the AquaTronic unit, which ensures correct motor rotation every time.

AquaTronic

The AquaTronic unit replaces the built-in contactor in the basic pump configurations and ensures that the motor always rotates correctly, no matter how the phases are connected. Key benefits of the AquaTronic unit include:

- Correction of motor rotation if phases are improperly connected
- Run mode
- Integrated start equipment (direct or soft start depending on pump model)
- Motor protection against high temperature, high amperage and missing phase

If the pump is also equipped with an optional Level sensor, AquaTronic provides:

- Precise level control
- Protection against dry running


AquaTronic Service Diagnostic Program

Connecting a PC to the AquaTronic unit via USB cable provides access to the Service Diagnostic Program, which offers:

- Pump status data (temp, voltage, moisture, etc.)
- Pump operating history
- Pump failure history
- Pump service and maintenance history
- Digital manual and spare parts documentation

AquaPlug and AquaTronic Control Panel

AquaPlug and AquaTronic Control Panel are options that combine with AquaTronic to provide additional alarm and start/stop functions, as well as indications for important parameters. AquaPlug is incorporated into the power line via 16A or 32A sockets.



Overview of Electronic Supervision Features

The table below shows the range of features available when the AquaTronic unit and other electronic supervision options are used with the submersible dewatering pumps XJ, XJC and XJS.

| Electronic supervision feature | Basic pump configuration with contactor | Pump with AquaTronic | Pump with AquaTronic + Level Sensor | Pump with AquaTronic + AquaPlug/ AquaTronic Control Panel | Pump with AquaTronic + AquaPlug/ AquaTronic Control Panel + Level Sensor |
|------------------------------------|---|----------------------|-------------------------------------|---|--|
| Run mode | ✓ | ✓ | ✓ | ✓ | ✓ |
| Integrated start equipment | ✓ | ✓ | ✓ | ✓ | ✓ |
| Automatic correction of rotation | | ✓ | ✓ | ✓ | ✓ |
| Motor protection – high temp | ✓ | ✓ | ✓ | ✓ | ✓ |
| Motor protection – high amp | | ✓ | ✓ | ✓ | ✓ |
| Protection against missing phase | | ✓ | ✓ | ✓ | ✓ |
| Level control | | | ✓ | | ✓ |
| Protection against dry running | | | ✓ | | ✓ |
| Automatic restart | | | ✓ | | ✓ |
| Stop mode | | | | ✓ | ✓ |
| E-mode (automatic stop/run) | | | | | ✓ |
| Indication of water in oil | | | | ✓ | ✓ |
| Indication of low motor insulation | | | | ✓ | ✓ |
| Indication of high/ low voltage | | | | ✓ ✓ | ✓ ✓ |
| Indication of high temp | | | | ✓ ✓ | ✓ ✓ |
| Indication of high amp | | | | ✓ ✓ | ✓ ✓ |
| Indication of phase imbalance | | | | ✓ ✓ | ✓ ✓ |
| USB cable connection | | ✓ | ✓ | ✓ | ✓ |

✓ ✓ = Fault indication when pump is automatically stopped to protect the motor

Pump Options and Accessories

AQUATRONIC UNIT FOR CORRECT MOTOR ROTATION

Our built-in AquaTronic unit integrates electronic intelligence into the pump, ensuring correct motor rotation by automatically adjusting for incorrect phase order. It also protects the motor by stopping the pump in the event of over-amperage, overheating, low or high voltage or missing phase. Another feature of the AquaTronic unit is the internal software that allows pump performance and service diagnostics data to be viewed on a PC via USB link, enabling accurate evaluation of service and maintenance needs. The workshop manual and spare parts list, readily available in the AquaTronic unit, can be viewed via the link as well. The AquaTronic unit must be ordered when ordering the pump. Retrofitting is not possible.



AQUAPLUG AND AQUATRONIC CONTROL PANEL

AquaPlug and AquaTronic Control Panel are options that combine with AquaTronic to provide additional alarm and start/stop functions, as well as indications for important parameters. AquaPlug is incorporated into the power line via 16A or 32A sockets.



LEVEL SENSOR FOR PRECISE AND COST EFFECTIVE WATER LEVEL CONTROL

Together with AquaTronic, the level sensor provides precise and cost-effective water level control, and helps lower power consumption.



SOFTDRIVE FOR COST EFFECTIVE OPERATION

Sulzer offers a built-in SoftDrive concept on the J 205 pumps. It reduces starting current dramatically and provides smooth operation for both the power net and pump equipment. The pump can be started with a smaller-sized generator compared to a standard pump started directly on-line.



QUICK AND EASY INSTALLATION WITH FLOATATION RING

Sulzer offers a solution for pumps up to 45 kg. The ring is easy to install and can be used with dewatering pumps J 12-15, XJ 25-40.



FLOATATION SYSTEM TO PREVENT UNNECESSARY WEAR

A modular floatation system is available, covering pumps from 59 to 600 kg. The modular floatation system is easy to build and used with dewatering pumps XJ 50-110, XJS 50-110, J 205-604.



PROTECTIVE BELTS FOR MORE DURABLE OPERATION

Sulzer submersible dewatering pumps can easily be fitted with zinc anode belts providing protection against galvanic corrosion. The cast parts of the pump can also be protectively coated, ensuring trouble-free operation when pumping salty or brackish water.



POLYURETHANE FOR PROLONGED DRAINAGE PUMP LIFE

Sulzer offers wear rings in polyurethane, which increases resistance when pumping fine sand and other abrasive mediums. Polyurethane-coated wear rings are available as an option on J 205-604.



SERIES CONNECTIONS FOR PUMPING HIGH HEADS

With minimal effort, the standard Sulzer drainage pumps can be rebuilt to function in series for high head applications.



BOTTOM SUCTION ADAPTER FOR TOTAL WATER REMOVAL

On pumps J 12-15 and J 24, the standard bottom plate may be replaced by a bottom suction adapter. A basement floor or a tank can be pumped practically dry with this adapter.



REPAIR KITS THAT SAVE TIME AND MONEY

Sulzer offers repair kits for all submersible dewatering pumps. The repair kits include common parts required for a typical repair. Our modular pump design makes it possible to repair all drainage and sludge pumps with just a few repair kits.

