



ROBOTIC, REFLECTORLESS AND MACHINE CONTROL FEATURES SATISFY ALL SITE POSITIONING AND MACHINE CONTROL NEEDS

INDUSTRY-LEADING 20 HZ DYNAMIC POSITIONING UPDATE RATE

ACTIVE TARGET FUNCTION GUARANTEES RELIABLE LOCK ON THE CORRECT TARGET

DR PLUS LONG-RANGE REFLECTORLESS MEASUREMENTS ELIMINATE THE RISK AND DELAY OF WALKING THE SURFACE WITH A TARGET

TRIMBLE MAGDRIVE SERVOS PROVIDE UNMATCHED INSTRUMENT TURNING AND TRACKING SPEEDS

THE ALL-IN-ONE, UNIVERSAL TOTAL STATION

The Trimble® SPS630, SPS730 and SPS930 Universal Total Stations can tackle any measurement, stakeout or machine control task on the job site— all from the same instrument. Universal Total Stations are packed with market leading features such as:

- Long life integrated batteries for a full day of interrupted work
- Bluetooth for cable free operation
- Choice of Trimble TSC3, Trimble Tablet, and TCU controllers to suit your site needs
- Intuitive SCS900 Site Controller Software
- Optional machine control mode

These features make the Universal Total Stations easy to use for all your jobsite needs. No matter what job you are doing, SPS total stations will deliver unmatched user experience, all round capability and incredible results.

DR Plus Long-Range Reflectorless Measurement

The DR Plus™ long-range reflectorless measurement capability allows you to measure hard-to-reach or unsafe places up to 2 kilometers (1.2 miles) away. There is no need to walk the surface with a target, so you'll increase productivity and safety when measuring stockpiles, profiling cuttings and rock faces.

Trimble MultiTrack Technology

Trimble MultiTrack™ technology locks on and tracks passive prisms for monitoring or control measurements and active targets for dynamic measurement, stakeout and grade control. Active targets guarantee lock to the correct target, especially in dusty construction site conditions. Up to 16 unique channels of target identification can be used to differentiate survey crews and grade checkers from machines eliminating down time caused by unnecessary interference.

Unmatched Dynamic Positioning

Trimble's patented MagDrive™ servo technology utilizes magnetic levitation to eliminate friction. Fast response time and fast servos allow the instrument to change direction, and track more reliably. Trimble Universal Total Stations can provide highly accurate machine guidance for excavation, grading, compaction, milling, and paving projects. Using the same Trimble total station, your machines can work to tight construction tolerances, save expensive materials, avoid rework and get to grade faster.



ANGLE MEASUREMENT

Horizontal Accuracy SPS630, SPS730, SPS930
 Standard deviation based on DIN 18723 5", 3", 1" (1.5, 1.0, 0.3 mgon)
 Vertical Accuracy SPS630, SPS730, SPS930
 Standard deviation based on DIN 18723 5", 2", 1" (1.5, 0.6, 0.3 mgon)
 Angle Reading (least count)
 Standard mode 1" (0.3 mgon)
 Tracking mode 2" (0.6 mgon)
 Dual-axis compensator ±6' (±100 mgon)

DISTANCE MEASUREMENT ACCURACY

Prism Mode
 Standard mode ±(2 mm + 2 ppm) ±(0.0065 ft + 2 ppm)
 Tracking mode¹ ±(4 mm + 2 ppm) ±(0.013 ft + 2 ppm)
 Synchronized angle and distance measurements Yes
 Position update rate Up to 20Hz
 DR Reflectorless Mode
 Standard mode ±(2 mm + 2 ppm) ±(0.0065 ft + 2 ppm)
 Scanning mode ±(4 mm + 2 ppm) ±(0.013 ft + 2 ppm)

MEASUREMENT RANGE

Prism Mode (under clear conditions^{2,3})
 1 prism 2,500 m (8,202 ft)
 1 prism (long range mode) 5,500 m (18,044 ft)
 DR Reflectorless Mode⁴
 Kodak Gray Card (18% reflective) >600 m (1969 ft)
 Kodak Gray Card (90% reflective) >1300 m (4265 ft)
 Servo system MagDrive servo technology, integrated servo/angle sensor, electromagnetic direct drive
 Rotation speed 115 degrees/sec (128 gon/sec)
 Clamps and slow motions Servo-driven, endless fine adjustment
 Positioning speed 180 degrees (200 gon) 3.2 sec

TELESCOPE

Magnification 30x
 Field of view 2.6 m at 100 m (8.5 ft at 328 ft)
 Shortest focusing distance 1.5 m (4.92 ft) – infinity
 Illuminated crosshair Variable (10 steps)

POWER SUPPLY

Internal battery Rechargeable Li-Ion battery 11.1 V, 4.4 Ah
 Operating time⁵ Approximately 6 hours on one internal battery

WEIGHT

Instrument with internal battery 5.25 kg (11.57 lb)

ROBOTIC SPECIFICATIONS

Range² 700 m (2,297 ft)
 Shortest search distance 0.2 m (0.65 ft)

ATS MODE FOR GRADE CONTROL

Range to target (MT900)^{1,2,3} 700 m (2,297 ft)
 Search time (typical)⁶ 2-10 s
 Search area 360 degrees (400 gon)
 or defined horizontal and vertical search window
 Maximum velocity of target
 Radial speed 114°/s
 Axial speed 6 m/s
 Data output
 Rate 20 Hz
 Timing ± 1 ms
 Latency over radio 40 ms
 Synchronized measurement data <1 ms
 Number of Target ID channels 16

Specifications subject to change without notice.

- 1 The accuracy statement is valid for a static target or a target moving at constant speed. During acceleration or deceleration, or a target moving with high speed >15 kph (9.3 mph) the accuracy will decrease.
- 2 Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.
- 3 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
- 4 Kodak Gray Card, number E1527795
- 5 The capacity at -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).
- 6 Dependent on selected size of search window.



www.ismar.is

Ismar
 Sidumuli 28
 Reykjavik, Iceland, 112
 Iceland
 5105100
 ismar@ismar.is

Trimble Heavy Civil Construction
 10368 Westmoor Drive
 Westminster, Colorado 80021 USA
 800-361-1249 (Toll Free)
 +1-937-245-5154 Phone
 construction_news@trimble.com



www.trimble.com