

# Trimble SiteVision

## OUTDOOR AUGMENTED REALITY SYSTEM



### KEY FEATURES

- ▶ Accurately places and displays 2D/3D data in real world context from any angle at true-to-life scale
- ▶ Precisely locates and reveals hidden assets
- ▶ Combines Trimble® Catalyst™ GNSS centimeter-level positioning and electronic distance measurement (EDM) with Google® AR technology
- ▶ Automatically transforms complex 2D designs into visual 3D models
- ▶ Switches between 2D and 3D views
- ▶ Provides Trimble cloud-based data hosting and reporting tools
- ▶ Enables collaboration and communication of designs on the job site
- ▶ Compatible with a wide range of Trimble, open industry standard, and third-party file formats
- ▶ Lightweight, portable handheld or pole-mounted unit

Learn more:  
[sitevision.trimble.com](https://www.trimble.com/sitevision)

\* Smartphone not included.



# Trimble SiteVision OUTDOOR AUGMENTED REALITY SYSTEM

HARDWARE	
SV INTEGRATED POSITIONING SYSTEM	
GNSS position accuracy	H <sub>z</sub> : 1 cm + 1 ppm RMS V <sub>t</sub> : 2 cm + 1 ppm RMS
GNSS constellations	GPS, GLONASS, Galileo, QZSS, SBAS, L-Band Satellite Corrections
Supported correction formats	RTCM 3.0, RTCM 3.1, RTCM 3.2, CMRx
EDM/AR position accuracy	Typical H <sub>z</sub> : < 20 cm rms at 10 m   V <sub>t</sub> : < 10 cm rms at 10 m (varies by phone model)
EDM distance measurement accuracy	Typically ±3 mm at -10 °C to +50 °C
EDM distance measurement range	Typically 0.3 m–25 m to fresh asphalt   Up to 100 m to white walls
EDM measuring time	0.1–4 seconds depending on surface, range & brightness
Power management	Swappable batteries ~ 2.5–3 hours per battery (varies by phone model)
Dimensions	Diameter: 135 mm   Height: 285 mm
Weight	560 g with battery
Operating temperature	-20 °C to +40 °C (-4 °F to +104 °F)
Operating temperature range with AR (phone)	Typically -10 °C to +35 °C (14 °F to +95 °F), varies by phone model
Storage temperature range	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	95% non condensing
Ingress protection	IP65
Drop	Drop 1.2 m (4')
User interface	LED for power on, Bluetooth connection status, low battery warning

\* Applies to Trimble SiteVision Integrated Positioning System only, not user provided mobile device.

SOFTWARE	
Model placement	Automatic with Georeferenced data   Measured (cm)   Manual
Supported formats	Trimble: SKP, VCL, TTM Open industry standards: IFC, LandXML 3rd party: DWG, SHP, GDB, PNG
Connectivity (model data)	Cellular or Wi-Fi, via user supplied mobile phone
Connectivity (correction data)	Cellular or Wi-Fi via user supplied mobile phone L-band satellite for remote operations
Data interpretation	User defined rules & 3D symbols
Measurement and recording functions	Georeferenced photo, ToDo's, Tasks, Points, Grade, Distance, Cut/Fill
Measurement methods	GNSS, EDM remote measurement, AR model measurement
Measurement modes	Model point to model point   Ground point to model point   Ground point to ground point
Validated Phone Models	Samsung S10+, Samsung S9+, Samsung Note 9, Samsung Note 8, running Android™ 9
Minimum Phone Requirements	Phone supported by Google Play Services for AR, running Android 9

SUBSCRIPTION INCLUDES	
GNSS correction services	SiteVision™ Precision Service including Trimble VRS Now™ and Trimble CenterPoint® RTX
Cloud storage	Trimble Cloud services

Specifications subject to change without notice.

© 2019, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo, and CenterPoint are trademarks of Trimble Inc., registered in the United States and in other countries. Catalyst, SiteVision and VRS Now are trademarks of Trimble Inc. Google, Google Play and other marks are trademarks of Google LLC. All other trademarks are the property of their respective owners. (08/19)