

Trimble TDC600

HANDHELD



KEY FEATURES

- All-in-one GNSS data collector and smartphone
- Android™ 8.0 operating system
- 6-inch high resolution sunlight-readable display
- Powerful Qualcomm[®] processor with 4 GB RAM and 64 GB internal storage
- Large capacity, user replaceable all day battery
- Real-time positioning with built-in GNSS receiver
- Google Mobile Services certified with access to Google Play™ store apps
- Ultra-rugged design with MIL-STD-810G certification
- 4G LTE, Wi-Fi, Bluetooth connectivity options for voice calls and data
- ► Ergonomic, lightweight and slim form factor
- Front- and rear-facing cameras
- Supports the Trimble® Catalyst™ service and Trimble R Series GNSS receivers
- Runs Trimble TerraFlex™, Trimble Access™, third-party or custom-developed field applications

Learn more: geospatial.trimble.com/tdc600



STANDARD FEATURES

- · Integrated 4G cellular data, text and voice capability
- 5 MP front camera and 13 MP rear camera
- Wi-Fi IEEE 802.11 a/b/g/n/ac, 2.4 GHz / 5 GHz dual-band
- 6.0 inch LED-backlight screen with capacitive multi-touch Long-life user replaceable Li-Ion battery
- 2.2 GHz Qualcomm Snapdragon™ 626 processor
- 4 GB RAM
- 64 GB flash memory¹
- 1 MicroSDHC memory card slotIntegrated speaker and microphone

OPERATING SYSTEM

- Android 8.0 (Oreo)
- Languages available: Afrikaans, Azebaijani, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hindi, Hungarian, Italian, Korean, Lithuanian, Norwegian (Bokmål), Polish, Portuguese (Portugal and Brazil), Romanian, Russian, Serbian (Cyrillic), Simplified Chinese, Spanish, Swedish, Turkish
- Software package includes: Google Mobile Services

COMMUNICATIONS²

- Cellular: GSM (850/900/1800/1900), WCDMA (B1/B2/B5/B8), LTE-FDD (B1/B2/ B3/B4/B5/B7/B8/B12/B13/B17/B20/B25/B28), LTE-TDD (B38/B39/B40/B41), TD-SCDMA (B34/B39)
- Wi-Fi IEEE 802.11 a/b/g/n/ac
- Bluetooth 4.1
- NanoSIM x 2
- USB 3.0 (Type-C)

STANDARD ACCESSORIES

- Hand strap
- A/C charger
- USB cable
- · Lanyard

OPTIONAL ACCESSORIES

- · External magnetic GPS antenna
- · Pole bracket
- Replacement batteries

SOFTWARE COMPATIBILITY

Please refer to the Product Compatibility matrix (www.trimble.com/mappingGIS/productcompatibility)

Trimble TDC600 HANDHELD

TECHNICAL SPECIFICATIONS

PHYSICAL Clock frequency: 2.2 GHz 4 programmable keys, standard Android touch panel 3 buttons, On screen keyboard Battery Li-lon removable battery Standard capacity 8000 mAh

ENVIRONMENTAL

NVIKONWENTAL
mperature
Operating20 °C to +55 °C (-4 °F to +131 °F)
Storage40 °C to 70 °C (-40 °F to 158 °F)
umidity95% non-condensing
ater & Dust proof IP67
ee drop 1.2 m (MIL-STD-810G)

INPUT/OUTPUT

	MicroSDHC memory card (up to 256 GB). Gorilla Glass 3, Optically bonded, AF coated, auto rotate
Resolution	1920 x 1080
	500 Cd/m²
Audio	Built-in microphone and speaker
	Audio jack through USB-C
	Pogo pin connector
	USB 3.0, external antenna connector
Digital camera	
Front camera	5 MP with fixed focus
Sensors	Ambient light sensor, digital compass, gyrometer, accelerometer, barometer

GNSS

GNSS Receiver	U-blox Neo-M8T
Internal antenna: 72 channels	GPS L1 C/A, GLONASS, BeiDou, SBAS
Integrated real-time	. SBAS (WAAS/EGNOS/MSAS/GAGAN/QZSS)
Tri constellation system	GPS/GAL, GPS/GLO/GAL or GPS/BeiDou/GAL
External antenna connector	Yes
Protocol	Location Services
	NMEA output (optional)

ACCURACY SPECIFICATIONS (HORIZONTAL RMS)3

- The actual available capacity of the internal memory is less than the specified capacity because the operating system and default applications occupy part of the memory. The available capacity may change when you upgrade applications or the device.
 Bluetooth, wireless LAN and cellular type approvals are country specific. Trimble TDC600 handheld has Bluetooth, wireless LAN and cellular approval in North America (excluding Verizon) and EU. For other countries, please consult your local Reseller.

 | Participated Note: No Province of Participated Verices of the Participated Verices of Participa
- please consult your local Reseller.

 Horizontal Root Mean Squared accuracy. Requires data to be collected using vertical mounting, minimum of 4 satellites, PDOP mask at 99. SNR mask at 12 dBHz, elevation mask at 5 degrees, and reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception.

 SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only, EGNOS (European Geostationary Navigation Overlay System) available in Europe only, and MSAS available in Japan only.



Contact your local Trimble Authorized Distribution Partner for more information

NORTH AMERICA

Trimble Inc. 10368 Westmoor Dr Westminster CO 80021 FUROPE

Trimble Germany GmbH Am Prime Parc 11 65479 Raunheim **GERMANY**

ASIA-PACIFIC

Trimble Navigation Singapore PTE Limited 3 HarbourFront Place #13-02 HarbourFront Tower Two Singapore 099254 SINGAPORE

© 2019–2020, Trimble Inc. All rights reserved. Trimble, and the Globe & Triangle logo are trademarks of Trimble Inc., registered in the United States and in other countries. Access, Catalyst and TerraFlex are trademarks of Trimble Inc. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under license. Android, Google and Google Play are trademarks of Google LLC. All other trademarks are the property of their respective owners. PN 022516-4390 (07/20)

